

	<b>Queen Anne's County Fire &amp; EMS Commission Operations Manual</b>	No. 06.09
		Effective Date: May 2, 2013
	<b>Quint and Telesquirt Standards</b>	Revised Date: January 9, 2014

**I. SCOPE**

- A. This standard applies to all Queen Anne's County Fire Department's.

**II. PURPOSE**

- A. To establish standards for a Quint or Telesquirt.

**III. RESPONSIBILITY**

- A. All Queen Anne's County Fire Department's will be responsible for ensuring strict adherence to this standard.

**IV. STANDARD**

- A. The vehicle shall consist of a motorized piece of apparatus of minimum capacity to carry the equipment below without being overloaded. The vehicle shall meet DOT specifications and shall not exceed chassis manufacturer's GVW. The vehicle shall be equipped with an audible back up alarm and necessary warning devices. It must be registered as an emergency vehicle and meet all codes of the Maryland Motor Vehicle Administration or its successors.

- B. To be numbered with 1 digit number.

- 1. Example; Quint 6.

- C. Minimum required equipment to be carried.

- 1. One two way radio to meet county standards and a portable radio with charger for each seat that contains an SCBA including the driver's seat.
- 2. A motor pumper pf at least 1000 gpm capacity.
- 3. Tank minimum 500 gallons.
- 4. Four portable electric hand lights.
- 5. Two 500 watt floodlights (mounted.)

	<b>Queen Anne's County Fire &amp; EMS Commission Operations Manual</b>	No. 06.09
		Effective Date: May 2, 2013
	<b>Quint and Telesquirt Standards</b>	Revised Date: January 9, 2014

6. Two 30 minute Breathing apparatus (pressure demand & pass devices  
For each) four spare bottles.
7. Two 500 watt floodlights (portable.)
8. One 5000 watt generator (mounted or portable.)
9. Four 12' x 18' salvage covers (minimum size.)
10. One battering ram.
11. Two 150' lengths of 9000 lb. Static kernmantle rope.
12. Three ladder belts.
13. One K-12 gas powered saw or equivalent with gas and oil.
14. Two wheel chocks.
15. Two 16" electric smoke ejector (minimum size) or positive pressure fan.
16. Two 24" closet hooks.
17. One bailing hook (optional)
18. Two door hangers mount for smoke ejector.
19. One crosscut saw.
20. Two flat head axes.
21. Two pick head axes.
22. One 20lb. Co2 extinguisher.
23. One 20lb dry chemical extinguisher.
24. One 2.5 gallon water extinguisher.
25. Two haligan tools 30"
26. Two bolt cutters 1 large and 1 small.
27. Two 8lb. Sledge hammers.
28. Two crowbars, 1 large and 1 small.
29. One 48" pry bar.
30. Two 30" Clemens hook.
31. Two grain shovels.
32. Two pitch forks.
33. Two street brooms.
34. Two mops.
35. One roll polyethylene ( 1200 sq ft )
36. Two 36" squeegees.
37. Two pointed spade shovels.
38. One electric submersible pump (1.5" optional.)
39. One electric junction box.
40. Four portable cord reels with 100 ft electric cord.

	<b>Queen Anne's County Fire &amp; EMS Commission Operations Manual</b>	No. 06.09
	<b>Quint and Telesquirt Standards</b>	Effective Date: May 2, 2013  Revised Date: January 9, 2014

41. One 3500 psi air cylinder (optional)
42. One ladder pipe 3" or pre-pipe.
43. One 2.5" siamese with shut off (optional.)
44. One adjustable gallon fog tip for ladder.
45. One set of stacked tips for ladder pipe.
46. Two 2.5" double male couplings.
47. Two 2.5" double female couplings.
48. Two hammers.
49. Two hatchets.
50. One tool box with assorted tools.
51. One 50' extension cord.
52. Two pair of staplers & scissors.
53. One first aid kit (NFPA 1903) and oxygen with liter flow.
54. One gas can.
55. Two 10 quart buckets.
56. One chimney sweep.
57. One pair heat resistant gloves.
58. Two hose straps.
59. Two sets 2.5" or greater spanner wrenches.
60. One adjustable hydrant wrench.
61. Two 6' ceiling hooks.
62. Two 10' ceiling hooks.
63. Two 12' ceiling hooks.
64. 115 ft of ground ladders (both extension and straight to be made of aluminum.)
65. One 10' folding attic ladder
66. One 75' minimum aerial device to be tested every two years (steel or aluminum.)
67. QAC ADC map book and all other in which you respond to an alarm.
68. 1000' of 3" hose or larger.
69. 400' of 1.5" to 2" hose nst coupling.
70. Four sprinkler wedges or stops.
71. One set emergency road triangles.
72. Two 1.5" nozzles shut off type, with combination fog and straight stream (95 gpm.)
73. One reducer 2.5" wye reducer with two 1.5" with shut off discharges.

	<b>Queen Anne's County Fire &amp; EMS Commission Operations Manual</b>	No. 06.09
		Effective Date: May 2, 2013
	<b>Quint and Telesquirt Standards</b>	Revised Date: January 9, 2014

- 74. One reducer 2.5" female to 1.5" male.
- 75. Assorted spare gaskets
- 76. One (1) Emergency Response Guidebook to Hazardous Materials for First Responders.

---

William H. Faust, Chairman  
Queen Anne's County Fire & EMS Commission